


CANADA ONLY
CANADA UNIQUEMENT



AMBIANCE®

FIREPLACES | BBQ | OUTDOORS | SPAS



INSTALLATION AND OPERATING INSTRUCTIONS **FREESTANDING STOVE LUXUS® FS24 V | STOVE LUXUS® FS28 V**

FR · MANUEL D'INSTALLATION ET D'UTILISATION · POÊLE AUTOPORTANT LUXUS® FS24 V | LUXUS® FS28 V

07.2025

INTRODUCTION AND UNIT DESCRIPTION FREE-STANDING STOVES LUXUS® FS24 V / FS28 V RANGE.

PLEASE READ THIS ENTIRE MANUAL BEFORE YOU INSTALL YOUR MODULAR FREESTANDING STOVE UNIT. PLEASE READ THE MANUAL FOR OPERATING INSTRUCTIONS AND HOW TO BURN THE FIRE THAT YOU HAVE A CLEAN AND EFFICIENT FIRE.

FAILURE TO FOLLOW INSTRUCTIONS MAY RESULT IN PROPERTY DAMAGE, BODILY INJURY, OR EVEN DEATH.

Save this manual and keep it in a safe place that it is easy to refer to it.

"DO NOT INSTALL IN A MOBILE HOME"

WARNING: DO NOT OVERFIRE.

IF THE STOVE TOP OR CHIMNEY OR CONNECTOR GLOW RED, YOU ARE OVERFIRING!
THIS IS DANGEROUS AND WILL VOID THE WARRANTY.

This wood heater has a manufacturer-set minimum low burn rate that must not be altered. It is against federal regulations to alter this setting or otherwise operate this wood heater in a manner inconsistent with operating instructions in this manual.

This range of stoves have been tested by ...

POLYTEST –

Polytests Services Inc.

695 B rue Gaudette,

St-Jean-sur-Richelieu

Québec, Canada, J3B 7S7

450.741.3636

www.polytests.com

AND ARE LISTED TO UL1482-2011 AND ULC S 627-21.

THEY ARE ALSO EPA CERTIFIED – U.S. ENVIRONMENTAL PROTECTION AGENCY Certified to comply with 2020 particulate emission standards using CORD WOOD LUXUS® FS24 V 1.67 g/hr LUXUS® FS24 V 1.14 g/hr

WARRANTY.

PLEASE REFER TO WARRANTY CONDITIONS IN THE MANUAL.

"U.S. ENVIRONMENTAL PROTECTION AGENCY Certified to comply with 2020 particulate emission standards using cord wood.

SAFETY INFORMATION



IF THE INFORMATION IN THESE INSTRUCTIONS IS NOT FOLLOWED EXACTLY, A FIRE OR EXPLOSION MAY RESULT CAUSING PROPERTY DAMAGE, PERSONAL INJURY OR DEATH. IMPROPER INSTALLATION, ADJUSTMENT, ALTERATION, SERVICE OR MAINTENANCE CAN CAUSE INJURY OR PROPERTY DAMAGE, BODILY INJURY OR EVEN DEATH. PLEASE READ ENTIRE MANUAL BEFORE YOU INSTALL AND USE YOUR APPLIANCE. THIS APPLIANCE HAS NOT BEEN TESTED WITH AN UNVENTED GAS LOG SET. TO REDUCE RISK OF FIRE OR INJURY, DO NOT INSTALL AN UNVENTED GAS LOG SET INTO THE APPLIANCE..

- This appliance can be very hot when burning.
- Combustible materials such as firewood, wet clothing, etc. placed too close can catch fire.
- Children and pets must be kept from touching the appliance when it is hot.
- The chimney must be sound and free of cracks. Before installing this unit, contact the local building or fire authority and follow their guidelines.
- Operate only with the door tightly closed.
- Do not use an elevated grate or otherwise raise the fire.
- At least 14 square inches (90.3 square centimeters) of outside air must be admitted to the room or directly to the unit through a 5" (127 mm) diameter pipe. Failure to provide this may starve other fuel burning appliances from an adequate air supply.
- Make sure not to create negative pressure in the installation room, e.g. by means of an exhaust fan

or similar mechanical blower, as this could affect the combustion off the wood insert or increase the possibility of smoke leakage.

- This appliance is designed to burn natural wood only. Higher efficiencies and lower emissions generally result when burning air dried seasoned hardwoods, as compared to softwoods or to green or freshly cut hardwoods.
- Do not burn green or freshly cut wood.
- Do not start a fire with chemicals or fluids such as gasoline, engine oil, etc.
- Do not burn treated wood, coal, charcoal, colored paper, cardboard, solvents or garbage.
- Do not let the appliance become hot enough for any part to glow red.
- KEEP THE STOVE TOP TEMPERATURE BELOW 700°F (371°C). Attempts to achieve heat output rates that exceed design specifications can result in steel distortion and damage.



WARNING

**HOT GLASS WILL CAUSE BURNS.
DO NOT TOUCH GLASS UNTIL COOLED.
NEVER ALLOW CHILDREN TO TOUCH GLASS.**

NOTICE

- **DO NOT DISCARD THIS MANUAL**
IMPORTANT OPERATING AND MAINTENANCE INSTRUCTIONS INCLUDED.
- READ, UNDERSTAND AND FOLLOW THESE INSTRUCTIONS FOR SAFE INSTALLATION AND OPERATION.
- LEAVE THIS MANUAL WITH PARTY RESPONSIBLE FOR USE AND OPERATION.

Caution.

Do not install in a transportable building.

Safe Wood-Burning Practices

When using your wood burning appliance, follow these guidelines for safe operation:

- Keep flammable items, like curtains, furniture, newspapers, and books, away from your appliance.
- Only use newspaper, dry kindling and all-natural or organic fire starters. Never start a fire with gasoline, kerosene, or charcoal starter.
- Do not burn wet or green (unseasoned) wood.
- Many wax and sawdust logs are made for open hearth wood insert only. Check your wood stove or wood insert operating instructions before using artificial logs.
- If you use manufactured logs, choose those made from 100 percent compressed sawdust.
- Build hot fires. For most appliances, a smoldering fire is not safe or efficient.
- Keep the doors of your wood-burning appliance closed unless loading or stoking the live fire. Harmful chemicals, like carbon monoxide, can be released into your home.
- Regularly remove ashes into a covered, metal container. Store the container outdoors on a nonflammable surface.
- Keep a fire extinguisher handy.

Do not burn:

1. Garbage
2. Lawn clippings or yard waste
3. Materials containing rubber, including tires
4. Materials containing plastic
5. Waste petroleum products, paints or paint thinners, or asphalt products
6. Materials containing asbestos
7. Construction or demolition debris
8. Railroad ties or pressure-treated wood
9. Manure or animal remains
10. Salt water driftwood or other previously salt water saturated materials
11. Unseasoned wood
12. Paper products, cardboard, plywood, or particleboard.

The prohibition against burning these materials does not prohibit the use of fire starters made from paper, cardboard, saw dust, wax and similar substances for the purpose of starting a fire in an affected wood heater. Burning these materials may result in release of toxic fumes or render the heater ineffective and cause smoke.


TABLE OF CONTENTS

1. Installation overview	4	7. Maintenance	22
2. Introduction	5	7.1 Ash removal procedures	22
2.1 Example of identification plate	6	7.2 Creosote formation and removal	22
2.2 Dimensions	7	7.3 Runaway or chimney fire	22
2.3 Specification	8	7.4 Chimney cleaning	23
2.4 General instructions	8	7.5 Glass replacement	23
2.5 General Information	8	7.6 Care of glass	23
2.6 Combustion air	9	7.7 Cleaning the glass ceramic sheet	23
2.6.1 Connection directly to the unit	9	8. Replacements	23
3. Installation planning	10	8.1 exploded view	24
3.1 Minimum clearances to combustibles	10	9. Troubleshooting	25
3.1.1 Placement from combustible materials	11	10. General warranty terms and conditions	25
4. Installation	12	10.1 General Information	25
4.1 Hearth Extension	12	10.2 Warranty period	25
4.1.1 LUXUS® FS24 V / FS28 V	12	10.3 Requirement of effectiveness for the warranty	25
4.2 Combustible wall chimney connector pass-throughs	13	10.4 Warranty exclusions	25
4.3 Chimney installation	15	10.5 Note	25
4.3.1 Listed chimneys	15	11. Service history	27
4.3.2 Examples of typical installations	15		
4.4 Convection	17		
5. Finishing	17		
5.1 Bricks and baffles installation	17		
6. Operation	19		
6.1 Fire extinguishers / smoke detectors	21	U.S. ENVIRONMENTAL PROTECTION AGENCY Certified	to operate this wood heater in a manner incon-
6.2 Fuel	21	to comply with 2020 particulate emission standards	sistent with operating instructions in this manual.
6.3 Lighting a fire	21	using cordwood STOVE LUXUS® FS24 V 1.67 g/hr and	This wood heater has a manufacturer-set minimum
6.3.1 Flash fire	22	LUXUS® FS28 V 1.14 g/hr, Method 28R.	low burn rate that must not be altered. It is against
6.3.2 Extended fire	22		federal regulations to alter this setting or otherwise
		This wood heater needs periodic inspection and repair	operate this wood heater in a manner inconsistent with
		for proper operation. It is against federal regulations	operating instructions in this manual.

SPECIFICATIONS MODULAR FREESTANDING STOVE
LUXUS® FS24 V / FS28 V:

1. INSTALLATION OVERVIEW

	LUXUS® Freestanding Stove	
	Stove LUXUS® FS24 V	Stove LUXUS® FS28 V
Weight of Module	262 lbs (119 kg)	334 lbs (151,5 kg)
Module exterior: Width/depth/height (inches)	24 3/16" 17" 22 1/8"	28 13/16" 18 1/2" 25 3/8"
Recommended amount of wood when fueling (lbs/kg) wood: 2-3 logs of wood of app. 17-21 inches / 43-53cm	1,8 kg/hr	2,1 kg/hr
Single wall connector stove pipe:	6" (153 mm)	6" (153 mm)
Chimney pipe - class A. UL-103 HT:	6" (153 mm)	6" (153 mm)
Optimal thermal output:	19,000 BTU	29,000 BTU/hr
Min. /Max. output (kW):	10,613 - 47,417 BTU/hr	13,000 - 49,000 BTU/hr
Tested EPA emission particulate rate:	1.67 g/hr	1.14 g/hr



CAUTION

Do not connect to or use in conjunction with any air distribution Ductwork.

CAUTION

NOT TO BE INSTALLED IN ANY FIREPLACE.

2. INTRODUCTION



The AMBIANCE®/LUXUS® freestanding stoves have been tested and certified by CSA based on the following standards: UL-1482 & Can/ULC S 627-21. EPA : U.S. ENVIRONMENTAL PROTECTION AGENCY Certified to comply with 2020 emission standards using cord wood. Before installing your Spartherm wood stove, PLEASE NOTE: THE LOCAL AUTHORITY HAVING JURISDICTION (MUNICIPAL BUILDING DEPARTMENT, FIRE PREVENTION BUREAU, ETC) SHOULD BE CONSULTED BEFORE INSTALLATION TO DETERMINE THE NEED TO OBTAIN A PERMIT. Please read this manual carefully before installing or using your wood stove. Incorrect installation may result in fire. To reduce the risk of fire, follow the installation instructions. Failure to do so may result in property damage, bodily injury or even death. Keep this manual handy so you can refer to it whenever necessary

WARNING

- HIS APPLIANCE IS HOT WHEN OPERATED AND CAN CAUSE SEVERE BURNS IF CONTACTED.
- ANY CHANGES OR ALTERATIONS TO THIS APPLIANCE OR ITS CONTROLS CAN BE DANGEROUS AND IS PROHIBITED:
- Do not operate appliance before reading and understanding operating instructions. Failure to operate appliance according to operating instructions could cause fire or injury.
- Before installing this appliance, contact the local building or fire authority and follow their guidelines.
- This appliance must be installed by a qualified installer.
- Do not use a wood stove module or other product not specified for use with this wood stove.
- Risk of burns. The appliance should be turned off and cooled before servicing.
- Do not operate without fully assembling all components.
- Risk of cuts and abrasions. Wear protective gloves

and safety glasses during installation. Sheet metal edges may be sharp.

- Children and adults should be alerted to the hazards of high surface temperature and should stay away to avoid burns or clothing ignition.
- Young children should be carefully supervised when they are in the same room as the appliance. Toddlers, young children and others may be susceptible to accidental contact burns. A physical barrier is recommended if there are at risk individuals in the house.
- To restrict access to an appliance or stove, install an adjustable safety gate to keep toddlers, young children and other at risk individuals out of the room and away from hot surfaces.
- Clothing or other flammable material must not be placed on or near the appliance. Objects placed in front of the appliance must be kept a minimum of 48" (1220 mm) away from the front face of the appliance.
- Due to high temperatures, the appliance should be located out of traffic and away from furniture and draperies.
- Ensure you have incorporated adequate safety measure to protect infants/toddlers from touching hot surfaces.
- Even after the appliance is out, the glass and/or screen will remain hot for an extended period of time.
- Check with your local hearth specialty dealer for safety screens and hearth guards to protect children from hot surfaces. These screens and guards must be fastened to the floor.
- Any safety screen or guard removed for servicing must be replaced prior to operating the appliance.
- Under no circumstances should this appliance be modified.
- This appliance must not be connected to a chimney flue pipe servicing a separate solid fuel burning appliance.
- Do not operate the appliance with glass door removed, cracked or broken. Replacement of the glass should be done by a licensed or qualified service person.
- Do not strike or slam shut the appliance glass door.
- Only doors / optional fronts certified with the unit are to be installed on the appliance.
- Keep the packaging material out of reach of children and dispose of the material in a safe manner. As with

all plastic bags, these are not toys and should be kept away from children and infants.

- If the appliance is not properly installed, a house fire may result. Do not expose the appliance to the elements (e.g. rain, etc.) and keep the appliance dry at all times. Wet insulation will produce an odour when the appliance is used.
- The chimney must be sound and free of cracks. Clean your chimney a minimum of twice a year and as required.
- Do not start a fire with chemicals or fluids such as gasoline, engine oil, etc.
- Your appliance requires periodic maintenance and cleaning. Failure to maintain your appliance may lead to smoke spillage in your home.
- Lower emissions generally result when burning air dried seasoned hardwoods, as compared to softwoods or too green or freshly cut hardwoods. Burning wet unseasoned wood can cause excessive creosote accumulation. When this is ignited it can cause a chimney fire that may result in a serious house fire.
- This appliance is designed to burn natural wood only. Do not burn treated wood, coal, charcoal, coloured paper, cardboard, solvents or garbage.
- Burn wood directly on the refractory bricks. Do not elevate grate or otherwise raise the fire.
- Do not store wood within appliance installation clearances or within the space required for re-fueling and ash removal.
- Ashes must be disposed in a metal container with a tight lid and placed on a non-combustible surface well away from the home or structure until completely cool.
- Ensure clearances to combustibles are maintained when building a mantel or shelves above the appliance. Elevated temperatures on the wall or in the air above the appliance can cause melting, discoloration or damage to decorations, a T.V. or other electronic components.
- Do not install this wood stove module in a factory-built wood stove unless certified with the wood stove.

Safety Information



Appareil de Chauffage à combustion solide
 Testé aux Normes: UL-1482-11, CANULUX S627-21
 U.S. Environment Protection Agency: Certified to comply with 2021
 Particulate emission standards using cord wood:
 emission rate 1,67 g/hr
 Model: Ambiance@ LUXUS® FS 24 V
 Date of Fabrication: 05/2023
 Mois/Année: 05/2023
 No de Serie: Ambiance@ LUXUS® FS 24 V - 040


[illegible]

CAUTION: Only operate the wood heater with the doors fully closed. Replicate glass only with original 4 mm Roxa, ceramic glass. Areas of the fireplace glass which are cracked or broken must be replaced with the same manufacturer's installation instructions. If provided with a hearth extension, the hearth extension must be installed according to the installation instructions! Air is needed for firebrick operation! At least 14 square inches (90.3 square centimeters) of free air must be provided for each cubic foot (28.3 liters) of firebrick (10.5mm) diameter pipe. Failure to provide this may starve other fuel burning appliances for adequate air supply. Do not obstruct air inlet and outlet in any way.

Do not use a firebrick insert or other products not specified for use with this product.

CAUTION: Gas logs shall be certified for the application. This unit is not designed for use with gas logs. The unit must be inspected and repaired by a qualified technician. This wood heater needs periodic inspection and repair for proper operation.

This wood heater needs periodic inspection and repair for proper operation. For further information and repairs, please refer to the operating instructions in the owner's manual.



À installer comme appareil de chauffage autonome en respectant les dégagements indiqués dans les instructions du fabricant. Ne pas installer de l'avant de l'appareil au bord de la

Single-wall connector pipe		Double-wall connector pipe		Touya de raccordement à paroi simple		Touya de raccordement à double paroi	
A	11" / 279mm	A	11" / 279mm	A	6 3/8" / 165mm	A	6 3/8" / 165mm
B	14" / 356mm	B	14" / 356mm	B	8" / 203mm	B	8" / 203mm
C	16" / 406mm	C	16" / 406mm	C	10" / 254mm	C	10" / 254mm
D	18" / 457mm	D	18" / 457mm	D	12" / 305mm	D	12" / 305mm
E	20" / 508mm	E	20" / 508mm	E	14" / 356mm	E	14" / 356mm
F	24" / 609mm	F	24" / 609mm	F	18" / 457mm	F	18" / 457mm
G	28" / 711mm	G	28" / 711mm	G	20" / 508mm	G	20" / 508mm
H	30" / 762mm	H	30" / 762mm	H	24" / 609mm	H	24" / 609mm
I	36" / 914mm	I	36" / 914mm	I	28" / 711mm	I	28" / 711mm
J	42" / 1067mm	J	42" / 1067mm	J	30" / 762mm	J	30" / 762mm
K	48" / 1219mm	K	48" / 1219mm	K	36" / 914mm	K	36" / 914mm
L	54" / 1372mm	L	54" / 1372mm	L	42" / 1067mm	L	42" / 1067mm
M	60" / 1524mm	M	60" / 1524mm	M	48" / 1219mm	M	48" / 1219mm
N	66" / 1676mm	N	66" / 1676mm	N	54" / 1372mm	N	54" / 1372mm
O	72" / 1829mm	O	72" / 1829mm	O	60" / 1524mm	O	60" / 1524mm
P	78" / 1981mm	P	78" / 1981mm	P	66" / 1676mm	P	66" / 1676mm
Q	84" / 2133mm	Q	84" / 2133mm	Q	72" / 1829mm	Q	72" / 1829mm
R	90" / 2286mm	R	90" / 2286mm	R	78" / 1981mm	R	78" / 1981mm
S	96" / 2438mm	S	96" / 2438mm	S	84" / 2133mm	S	84" / 2133mm
T	102" / 2591mm	T	102" / 2591mm	T	90" / 2286mm	T	90" / 2286mm
U	108" / 2743mm	U	108" / 2743mm	U	96" / 2438mm	U	96" / 2438mm
V	114" / 2895mm	V	114" / 2895mm	V	102" / 2591mm	V	102" / 2591mm
W	120" / 3048mm	W	120" / 3048mm	W	108" / 2743mm	W	108" / 2743mm
X	126" / 3200mm	X	126" / 3200mm	X	114" / 2895mm	X	114" / 2895mm
Y	132" / 3352mm	Y	132" / 3352mm	Y	120" / 3048mm	Y	120" / 3048mm
Z	138" / 3505mm	Z	138" / 3505mm	Z	126" / 3200mm	Z	126" / 3200mm
AA	144" / 3657mm	AA	144" / 3657mm	AA	132" / 3352mm	AA	132" / 3352mm
AB	150" / 3810mm	AB	150" / 3810mm	AB	138" / 3505mm	AB	138" / 3505mm
AC	156" / 3962mm	AC	156" / 3962mm	AC	144" / 3657mm	AC	144" / 3657mm
AD	162" / 4114mm	AD	162" / 4114mm	AD	150" / 3810mm	AD	150" / 3810mm
AE	168" / 4267mm	AE	168" / 4267mm	AE	156" / 3962mm	AE	156" / 3962mm
AF	174" / 4419mm	AF	174" / 4419mm	AF	162" / 4114mm	AF	162" / 4114mm
AG	180" / 4572mm	AG	180" / 4572mm	AG	168" / 4267mm	AG	168" / 4267mm
AH	186" / 4724mm	AH	186" / 4724mm	AH	174" / 4419mm	AH	174" / 4419mm
AI	192" / 4877mm	AI	192" / 4877mm	AI	180" / 4572mm	AI	180" / 4572mm
AJ	198" / 5029mm	AJ	198" / 5029mm	AJ	186" / 4724mm	AJ	186" / 4724mm
AK	204" / 5182mm	AK	204" / 5182mm	AK	192" / 4877mm	AK	192" / 4877mm
AL	210" / 5334mm	AL	210" / 5334mm	AL	198" / 5029mm	AL	198" / 5029mm
AM	216" / 5487mm	AM	216" / 5487mm	AM	204" / 5182mm	AM	204" / 5182mm
AN	222" / 5639mm	AN	222" / 5639mm	AN	210" / 5334mm	AN	210" / 5334mm
AO	228" / 5792mm	AO	228" / 5792mm	AO	216" / 5487mm	AO	216" / 548

Important: Unit cannot use small base A on non-combustible material – must be 9 1/4" / 235mm off the floor from bottom of glass

IN FRONT OF UNIT –
Recommend amount of wood:
1.8 kg/ltr
1.8 kg/ltr

Important: l'appareil ne peut pas utiliser une petite base A sur un matériau incombustible – doit être à 9 1/4" / 235mm du sol à partir du bas du verre

Quantité de bois recommandée:
1,8 kg/ltr
1,8 kg/ltr

Min. test output (kW)	Min. test output (kW)
10813 = 47.47 BTU/hr	10813 = 47.47 BTU/hr
* Not tested - NFPA Guidelines in the USA, CAN/CSA B365-M91 in Canada. Floor protection must be minimum 3/8-inch non-combustible material extending beneath the stove, and to the front and sides from door opening and to the rear as indicated.	* Not tested - Exigences NFPA aux Etats-Unis, CAN/CSA B365-M91 au Canada. La protection de sol doit avoir une épaisseur de 3/8 pouces (1 cm), être d'un matériau non combustible et être placée devant et à côté de la porte ainsi qu'à l'arrière, comme indiqué.

[illegible]

DO NOT REMOVE THIS LABEL

Safety Information



Informations Sur La Sécurité




AMBIANCE®

Solid Fuel Room Heater - For Use with Solid Wood Fuel only	Apparatus de Chauffage à Combustion Solide
Model: LUXUS® FS 28 V	Modèle: Ambiance® LUXUS® FS 28 V
Date of Manufacture: Month/Year: 03/2024	Date de Fabrication: Mois/Année: 03/2024
Serial Number: Ambiance® LUXUS® FS 28 V-003	No de Série: Ambiance® LUXUS® FS 28 V-003
U.S. Environmental Protection Agency: Certified to comply with 2021 Particulate emission standards using cord wood emission rate 1.67 g/hr. U.S. Environment Protection Agency: Certified to comply with 2021 Particulate emission standards using cord wood emission rate 1.67 g/hr. WARNING: do not obstruct the space beneath the heater. Neoburner gas has overtures of gas for combustion, therefore, no gas adjustment is required. Avertissement: neoburner gaz a des ouvertures de gaz pour la combustion, donc aucune réglage de gaz n'est requis.	
U-1482-11 CANULS S92-23	U-1482-11 CANULS S92-23
Tested and approved by: CANULS S92-23	Testé et approuvé par: CANULS S92-23

[illegible][illegible]

Consult the owner's manual for further information. It is against federal regulations to operate this wood heater in a manner inconsistent with the operating instructions in the owner's manual.



Floor protection for Canada: 18" (457mm)
from unit to front of floor protector

[illegible]

Important: Unit cannot use small base A on non-combustible material - must be 9 1/4" x 235mm off the floor from bottom of glass	Important: Important ne peut pas utiliser une petite base A sur un matériau non-combustible. L'unité doit être à 9 1/4" x 235mm du sol à partir du bas du verre
IN FRONT OF UNIT *	DEVANT L'APPAREIL *
Recommend amount of wood: 2.1 kg/ltr	Quantité de bois recommandée: 2.1 kg/ltr

Min. / Max. tested (kW)	13,129 – 29,542 BTU/hr	Min. / Max. tested (kW)	13,129 – 29,542 BTU/hr
Not Tested – NFPA Guidelines in the USA, CANVISA B365-M81 in Canada, Flap protection must be minimum 3/8-inch non-combustible material extending beneath the stove, and to the front and sides from door		Not tested – Exigences NFPA aux États-Unis, CANVISA B365-M81 au Canada, La protection de sol doit avoir une épaisseur de 3/8 po (1 cm). Les flaps d'un matériau non combustible doivent être placés devant et à côté de la porte	




CAUTION: OPERATION. DO NOT TOUCH. KEEP CHILDREN AND CLOTHING AWAY. CONTACT MAY CAUSE SKIN BURNS. SEE NAME PLATE AND INSTRUCTIONS. KEEP FURNISHINGS AND OTHER DISTANCE AWAY FROM THE APPLIANCE. NOT SUITABLE FOR MOBILE HOME INSTALLATION. DO NOT OVERFIRE—IF HEATER OR CHIMNEY CONNECTOR

ATTENTION: FONCTIONNEMENT — NE PAS TOUCHER. TENIR LOIGNES LES ENFANTS ET LES VÊTEMENTS. LE CONTACT PEUT CAUSER DES BRÛLURES. CONSULTEZ LA PLAQUE D'IMMATRICULATION ET LES INSTRUCTIONS. GARDER LES MEUBLES ET AUTRES OBJETS DISTANCE DES APPAREILS. NE PAS INSTALLER DANS UNE MAISON MOBILE. ÉVITER DE SURCHAUFFER—SI LE FOU OU LA CHEMINÉE




GLOWS, YOU ARE OVERKIND,
 BECOMES RED, YOU SURCHAUFFEZ;
 DO NOT REMOVE THIS LABEL
 NE PAS ENlever ETIQUETTE

2.2 DIMENSIONS

	Stove LUXUS® FS24 V
A	17" / 432 mm / 424 mm
B	24 3/16" / 615 mm
C	22 1/8" / 562 mm
D	6" / 152 mm



	Stove LUXUS® FS28 V
A	18 1/2" / 470 mm
B	28 13/16" / 732 mm
C	25 3/8" / 644 mm
D	6" / 152 mm



2.3 SPECIFICATION

Conversion Factors

	Fire chamber volume	Minimum Power	Maximum power	Efficiency	Chimney type	Unit weight	Ideal fuel size
Stove LUXUS® FS24 V	0.95 ft³	10,613 BTU/hr	47,417 BTU/hr	70.29 %	6"	262 lbs	17"
Stove LUXUS® FS28 V	1.58 ft³	13,129 BTU/hr	49,000 BTU/hr	66.77 %	6"	334 lbs	21"

Inches to millimeters (mm): 1" = 25.4 mm

British Thermal Unit BTU/hr to Watt: 1 BTU/hr = 0.293 Watt

Kilogram to Pound: 1 kg = 2.205 lb

Cubicmeter to cubicfeet:

$$1\text{m}^3 = 35.314\text{ ft}^3$$

2.4 GENERAL INSTRUCTIONS



THIS APPLIANCE HAS NOT BEEN TESTED WITH ANY VENTED OR UNVENTED GAS LOG SET: TO REDUCE RISK OF FIRE OR PREVENT INJURY, DO NOT INSTALL A VENTED OR UNVENTED GAS LOG SET INTO THE APPLIANCE.

2.5 GENERAL INFORMATION

The chimney vent system used on your wood burning appliance should be designed with the least amount of restriction possible to enable the exhaust products to easily flow through it. Chimney vent systems that are too short or too long (refer to point 4.3 "chimney installation") can also have an adverse affect on the flow of exhaust through it. The wood burning appliance and chimney vent system also require a sufficient supply of combustion air not only to support the combustion in the combustion chamber but to replace the exhaust leaving it so it can flow freely up through the vent system and out into the atmosphere. It is the correct balance of combustion air and the chimney vent system that will ensure the appliance provides you with its optimum performance.

Be sure to provide sufficient combustion air. There are many other appliances in your home competing for air such as a kitchen range hood, forced air heating devices or a bathroom exhaust fan.



WARNING

Use only Spartherm specified components.

ANY ALTERATION TO OR SUBSTITUTION FOR ITEMS IN THIS SYSTEM, UNLESS ALLOWED BY THESE INSTALLATION INSTRUCTIONS, WILL VOID THE LISTING AND MAY VOID THE PRODUCT WARRANTY. IT MAY ALSO CREATE A HAZARDOUS INSTALLATION.

Expansion / contraction noises during heating up and cooling down cycles are normal and to be expected.

After extended periods of non-operation such as following a vacation or a warm weather season, the appliance may emit a slight odour for a few hours. This is caused by dust particles on the firebox burning off. Open a window to sufficiently ventilate the room.

CALIFORNIA PROP 65 WARNING:

Use of this product may produce smoke which contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

If you experience smoking problems, you may need to open a door, a window or otherwise provide some method of supplying combustion air to the appliance.

CAUTION:

The Spartherm modular freestanding stoves are not certified for gas log sets.

DO NOT CONNECT THIS APPLIANCE TO A CHIMNEY FLUE SERVING ANOTHER APPLIANCE.

This appliance and the components ARE DESIGNED TO BE INSTALLED AND OPERATED AS A SYSTEM. ANY ALTERATION TO OR SUBSTITUTION FOR ITEMS IN THIS SYSTEM, UNLESS ALLOWED BY THESE INSTALLATION INSTRUCTIONS, WILL VOID THE LISTING AND MAY VOID THE PRODUCT WARRANTY. IT MAY ALSO CREATE A HAZARDOUS INSTALLATION. READ THROUGH THESE INSTRUCTIONS THOROUGHLY BEFORE STARTING YOUR INSTALLATION AND FOLLOW THEM CAREFULLY THROUGHOUT YOUR PROJECT.

- Before beginning your installation, consult with your local building code agency or fire officials and insurance representative to ensure compliance
- Non-toxic smoke will be emitted during the paint curing process, to help dissipate the smoke open a window near the appliance.
- Remove any dust or debris off the top of the appliance before firing the appliance as the paint will become soft as the appliance heats up and will harden as the appliance cures. To cure the paint on your appliance burn your appliance moderately hot during the first few fires.
- To keep the gasket from sticking to the appliance as the paint is curing, periodically open the door every 5-10 minutes.
- For the first two weeks use generous amounts of fuel and burn the appliance for an hour as the appliance goes through a process of eliminating moisture in the steel and refractory bricks. The initial heat output will be reduced while the moisture is being drawn from the appliance and it will be necessary to build several hot fires to remove this moisture. DURING THIS PROCESS DO NOT OVERFIRE THE APPLIANCE.

**NATIONAL
FIREPLACE
INSTITUTE**



CERTIFIED

www.nficertified.org

We suggest that our woodburning hearth products be installed and serviced by professionals who are certified in the U.S. by the National Fireplace Institute® (NFI) as NFI Woodburning Specialists or who are certified in Canada by Wood Energy Technical Training (WETT).




**Wood Energy
Technical Training**
W E T T . C A N A D A

2.6 COMBUSTION AIR


when mounting the air system ensure that the air control system provides fresh air from the outside. In order for the air system to function, you have to ensure in the structure that no vacuum occurs in the housing. If convection grates are installed, be sure not to block them. Air system (accessory) is connected to the bottom of the stove.

LUXUS® FS24 V / FS28 V Backside air intake



2.6.1 CONNECTION DIRECTLY TO THE UNIT

To connect the separate combustion air directly to the unit you need to have the right separate combustion air connector Ø 4". Fix the connector directly to the unit. It can be oriented to the left side, right side or to the back.



Grills

The combustion air ducts will be protected at the outside by a grill. The free passage section of those grills is at least equivalent to the section of the air inlet. Please note that the infiltration of water and the effect of the wind can damage the system.

CLOSURE VALVE

If you decide to connect separate combustion air it is mandatory to install a closure valve to prevent condensate formation and to prevent the room from becoming cold while the stove is not in use. It should ideally be located as close as possible to the outside wall. It can be controlled from inside if it is not too far from the stove (cable length = 47").



PLEASE NOTE: COMBUSTION AIR INTAKE REQUIREMENTS.

It is recommended that the 4" Combustion air intake duct is installed in a correct manner.

Please find the following information.

Outside Air- ducts must...

- Be protected on the outside by a grill where the free passage section of this grill is at least equivalent to the section of the air inlet.

Please note that the infiltration of wind, weather, snow and water can effect or damage the air combustion system.

- Ideally be fitted with a butterfly valve so that it can manually, be used to close the cold air from entering the firebox.

Please note that the butterfly valve has to be 100% open or 100% closed and should not be used to adjust bur rate!

Try to keep the butterfly valve as close to the outside wall as possible.

- The air-duct should be insulated and the distance from the wood stove to the outside should be as short as possible.

For 4" air duct please refer to the maximum lengths and elbows

Number of 90 degree elbows

4' = 4 elbows

8' = 4 elbows

10' = 2 elbows

12' = 0 elbow

If you exceed these guidelines, you must compensate by using a larger diameter and/or a smoother duct. Careful not to crush the duct!

It should ideally be located as close as possible to the outside wall.

- If it is not possible to bring in combustion air to the wood stove please insure that there is sufficient air to feed the wood stove in the room – please note that this is not ideal.

Please contact your dealer who offers suitable parts for air inlet ducts (pipes and damper).

Make sure that the wire mesh is mounted at the combustion air inlet.

3. INSTALLATION PLANNING

Clean all ashes out of the inside of the existing wood stove opening. Make sure that the chimney and wood stove are free of cracks, loose mortar, creosote deposits, blockage or other signs of deterioration. If necessary, have any repair work done by a qualified professional before installing the module.

Do NOT remove bricks or mortar from the wood stove.

In case of an outside air inlet or ash dump, fill with fiberglass insulation. Adhere to minimum clearances as illustrated.



WARNING

WEAR GLOVES AND SAFETY GLASSES FOR PROTECTION.

CAREFULLY FOLLOW THE INSTRUCTIONS FOR ASSEMBLY OF THE PIPE AND OTHER PARTS NEEDED TO INSTALL THE APPLIANCE. FAILURE TO DO SO MAY RESULT IN A FIRE, ESPECIALLY IF COMBUSTIBLES ARE TOO CLOSE TO THE APPLIANCE OR CHIMNEY AND AIR SPACES ARE BLOCKED, PREVENTING THE FREE MOVEMENT OF COOLING AIR. DO NOT DRAW OUTSIDE AIR FROM GARAGE SPACES. EXHAUST PRODUCTS OF GASOLINE ENGINES ARE HAZARDOUS. DO NOT INSTALL OUTSIDE AIR DUCTS SUCH THAT THE AIR MAY BE DRAWN FROM ATTIC SPACES, BASEMENTS OR ABOVE THE ROOFING WHERE OTHER HEATING APPLIANCES OR FANS AND CHIMNEYS EXHAUST UTILIZE AIR. THESE PRECAUTIONS WILL REDUCE THE POSSIBILITY OF APPLIANCE SMOKING OR AIR FLOW REVERSAL. THE OUTSIDE AIR INLET MUST REMAIN CLEAR OF LEAVES, DEBRIS ICE AND/OR SNOW OR ANY OTHER OBSTACLES. IT MUST BE UNRESTRICTED WHILE APPLIANCE IS IN USE TO PREVENT ROOM AIR STARVATION WHICH CAN CAUSE SMOKE SPILLAGE AND AN INABILITY TO MAINTAIN A FIRE. SMOKE SPILLAGE

CAN ALSO SET OFF SMOKE ALARMS. NEGATIVE PRESSURE WITHIN YOUR HOME MAY INADVERTENTLY AFFECT YOUR APPLIANCE. TO PREVENT CONTACT WITH SAGGING OR LOOSE INSULATION, THE APPLIANCE MUST NOT BE INSTALLED AGAINST VAPOUR BARRIERS OR EXPOSED INSULATION. LOCALIZED OVERHEATING COULD OCCUR AND A FIRE COULD RESULT. DO NOT USE MAKESHIFT COMPROMISES DURING INSTALLATION. DO NOT BLOCK OR RESTRICT AIR, GRILLE OR LOUVRE OPENINGS. DO NOT ADD A HOOD. KEEP HAND TOOLS IN GOOD CONDITION; SHARPEN CUTTING EDGES AND MAKE SURE TOOL HANDLES ARE SECURE. ALWAYS MAINTAIN THE MINIMUM AIR SPACE REQUIRED TO THE ENCLOSURE TO PREVENT FIRES. DO NOT PACK REQUIRED AIR SPACES WITH INSULATION OR OTHER MATERIALS. COMBUSTION AIR INLET DUCTS ARE NOT TO TERMINATE IN ATTIC SPACES OR CRAWL SPACES.

3.1 MINIMUM CLEARANCES TO COMBUSTIBLES

DO NOT PLACE ANY COMBUSTIBLE MATERIALS (FURNITURE, FIREWOOD, ETC.) WITHIN 48" (1220 mm) IN FRONT OF THE Module.



COMBUSTIBLE MATERIALS CAN'T PROTRUDE ONTO THE METAL PARTS OF THE UNIT, THEY MUST BE COVERED WITH NON COMBUSTIBLE MATERIALS.



WARNING

Chimney connections shall not pass through an attic or roof space, closet or similar concealed space, or floor or ceiling. Where passage through a wall, or partition of combustible construction is desired, the instructions shall require that the installation conform to CSA B365, Installation code for Solid-Fuel-Burning Appliances and Equipment.

3.1.1 PLACEMENT FROM COMBUSTIBLE MATERIALS



The floor in front of the wood stove requires thermal protection. This protection must be non-combustible. Also this floor protector must be listed to UL 1618 ember protection. Do NOT install in a mobile home


	Single-wall connector pipe	Double-wall connector pipe
A	11" / 279 mm	11" / 279 mm
B	16 1/2" / 419 mm	6 1/4" / 158,8 mm
C	18" / 457 mm	8" / 203 mm
D	8" / 203 mm	8" / 203 mm
E	21" / 533 mm	21" / 522 mm
F	22" / 559 mm	21 3/4" / 553 mm
G	48" / 1219 mm	48" / 1219 mm

Distance to furniture

The recommend minimum distance from stove to furniture is 48 inches. Note that some furniture is more easily affected by heat and may need to be moved to greater distance. This is your responsibility.

In addition other combustible materials, away from the stove. In general, a distance of 48 inches must be maintained between the stove and moveable combustible item such as drying clothes, newspapers, firewood etc. Failure to meet the required clearances can endanger property and personal safety.

NOTE:



Valid for Stove LUXUS® FS24 V / FS28 V.

Important: Unit cannot use small base A on non combustible material - must be 9 1/2" off the floor from bottom of glass or 4 1/2" with r value 2,957 (Canada) or 6 1/2" with r value 2,957 (USA).

Acid Protection

If acid-washing the masonry around the stove, protect the stove surface with an acid-proof cover..

	clearance with single wall pipe	clearance with double wall pipe
A - backwall to unit	21" / 522 mm	11" / 279 mm
B - backwall to centre of the pipe	21" / 533.40 mm	11" / 279.40 mm
C - front wall / furniture	48" / 1219 mm	48" / 1219 mm
D - ceiling or alcove to bottom	84" / 2134 mm	84" / 2134 mm
E - floor to bottom of glass	9 1/2" / 241 mm or 4 1/2" - with r value 2,957 (Canada) 6 1/2" - with r value 2,957 (USA)	9 1/2" / 241 mm or 4 1/2" - with r value 2,957 (Canada) 6 1/2" - with r value 2,957 (USA)

4. INSTALLATION

4.1.1 LUXUS® FS24 V / FS28 V


4.1 HEARTH EXTENSION

**WARNING**

INSTALL THE HEARTH EXTENSION ONLY AS ILLUSTRATED!

A 16" / 406 mm for USA, 18" / 459 mm for Canada, minimum hearth extension in front of the stove made of non combustible material is required. In front of the unit, the hearth extension must extend 8" / 203 mm on each side. Also there must an hearth extension under the unit, which extend 8" on the rear side.

The non combustible material that is used must be UL 1618.



	clearances	description
A	8" / 203 mm Canada 6" / 152 mm USA	each clearances side of unit
B	8" / 203 mm	hearth extension on the rear side
C	16" / 406 mm for USA 18" / 459 mm for Canada	hearth extension length
D	single wall pipe = 18" / 475 mm double wall pipe = 8" / 203 mm	back wall to pipe

Caution.
Combustion air openings are not to be obstructed.

All floor protection materials must be non-combustible material.


FLOOR PROTECTOR MUST BE LISTED TO UL 1618 ember protection.

FLOOR PROTECTION TO COMPLY WITH CSA B365 IN CANADA

MODULE CLEARANCES

Configuration	SIDE WALL TO UNIT	SIDE WALL TO PIPE	BACK WALL TO UNIT	BACK WALL TO PIPE	CEILING OR ALCOVE TO BOTTOM OF UNIT
STRAIGHT single wall pipe	11" / 279 mm	22" / 559 mm	16 1/2" / 412 mm	18" / 457 mm	84" / 2134 mm
STRAIGHT double wall pipe	11" / 279 mm	21 3/4" / 553 mm	6 1/4" / 159 mm	8" / 203 mm	84" / 2134 mm
CORNER	8" / 203 mm	18" / 457 mm	8" / 203 mm	18" / 457 mm	84" / 2134 mm

4.2 COMBUSTIBLE WALL CHIMNEY CONNECTOR PASS-THROUGHS




METHOD A: 12" (304.8 MM) CLEARANCE TO COMBUSTIBLE WALL MEMBER:

Using a minimum thickness 3.5" (89 mm) brick and a 5/8" (15.9 mm) minimum wall thickness clay liner, construct a wall pass-through. The clay liner must conform to ASTM C315 (Standard Specification for Clay Fire Linings) or its equivalent. Keep a minimum of 12" (304.8 mm) of brick masonry between the clay liner and wall combustibles.

The clay liner shall run from the brick masonry outer surface to the inner surface of the chimney flue liner but not past the inner surface. Firmly grout or cement the clay liner in place to the chimney flue liner.



METHOD B: 9" (228.6 MM) CLEARANCE TO COMBUSTIBLE WALL MEMBER:



Using a 8" (203.2 mm) inside diameter, listed, factory-built solid-pack chimney section with insulation of 1" (25.4 mm) or more, build a wall pass-through with a minimum 9" (228.6 mm) air space between the outer wall of the chimney length and wall combustibles.

Use sheet metal supports fastened securely to wall surfaces on all sides, to maintain the 9" (228.6 mm) air space. When fastening supports to chimney length, do not penetrate the chimney liner (the inside wall of the solid-pack chimney). The inner end of the solid-pack chimney section shall be flush with the inside of the masonry chimney flue, and sealed with a non-water soluble refractory cement. Use this cement to also seal the brick masonry penetration.

Minimum chimney clearance
to sheet steel supports and
combustibles 2 in. (50.8 mm)



Two ventilated air
channels each
1 in. (25.4 mm).
Construction of
sheet steel.

METHOD C: 6" (152.4 MM) CLEARANCE TO COMBUSTIBLE WALL MEMBER:



Starting with a minimum 24 gage (.024" [.61 mm]) 8" (203.2 mm) metal chimney connector, and a minimum 24 gage ventilated wall thimble which has two air channels of 1" (25.4 mm) each, construct a wall pass-through. There shall be a minimum 6" (152.4 mm) separation area containing fiberglass insulation, from the outer surface of the wall thimble to wall combustibles. Support the wall thimble, and cover its opening with a 24-gage minimum sheet metal support. Maintain the 6" (152.4 mm) space. There should also be a support sized to fit and hold the metal chimney connector. See that the supports are fastened securely to wall surfaces on all sides. Make sure fasteners used to secure the metal chimney connector do not penetrate chimney flue liner.

METHOD D: 2" (50.8 MM) CLEARANCE TO COMBUSTIBLE WALL MEMBER:

Start with a solid-pack listed factory built chimney section at least 12" (304 mm) long, with insulation of 1" (25.4 mm) or more, and an inside diameter of 8" (2 inches [51 mm] larger than the 8" [203.2 mm] chimney connector). Use this as a pass-through for a minimum 24-gage single wall steel chimney connector. Keep solid-pack section concentric with and spaced 1" (25.4 mm) off the chimney connector by way of sheet metal support plates at both ends of chimney section. Cover opening with and support chimney section on both sides with 24 gage minimum sheet metal supports. See that the supports are fastened securely to wall surfaces on all sides. Make sure fasteners used to secure chimney flue liner.

METHOD E:

OR use a certified wall pass through.



4.3 CHIMNEY INSTALLATION

4.3.2 EXAMPLES OF TYPICAL INSTALLATIONS

This wood stove is designed and approved for installation with the following brands of chimneys measuring 6" and 7" (152 and 178 mm) in diameter as well as a minimum of 15' (4.6 m) and maximum of 45' (13.5m) in height.

4.3.1 LISTED CHIMNEYS

This appliance must be installed with a listed 6"/153 mm and 7"/178.5 mm chimney system approved under the following standards: CAN-ULC S629(IN CANADA) OR UL 103HT(N U.S.).

MAINTAIN CLEARANCES TO COMBUSTIBLES AS SPECIFIED IN THE CHIMNEY MANUFACTURERS INSTALLATION INSTRUCTIONS. YOU MUST FOLLOW THE CHIMNEY MANUFACTURER'S INSTALLATION INSTRUCTIONS FOR INSTALLATION OF ALL CHIMNEY COMPONENTS. USE APPROPRIATE SUPPORTS, CAPS, FLASHING AND SHIELDS IN ACCORDANCE WITH THE CHIMNEY MANUFACTURERS INSTALLATION INSTRUCTIONS.

CAUTION: THE STRUCTURAL INTEGRITY OF THE FLOOR, WALL AND CEILING/ROOF MUST BE MAINTAINED.

The table below shows the minimum chimney height requirements, wood stove included, according to the number of elbows:

chimney	number of elbows	minimum height
straight installation	-	15' (4.6 m)
1 - 15° offset	2 - 15° elbows	15' (4.6 m)
2 - 15° offset	4 - 15° elbows	18' (5.5 m)
1 - 30° offset	2 - 30° elbows	15' (4.6 m)
2 - 30° offset	4 - 30° elbows	20' (6.1 m)
* 1 - 45° offset	* 2 - 45° elbows	16' (4.9 m)
* 2 - 45° offset	* 4 - 45° elbows	23' (7.0 m)



* permitted only in Canada

Refer to building code to make sure the installation seals the penetration of the building envelope or refer to the listed chimney installation manual.


**WARNING**

The chimney and the required chimney connector must be in a good condition and kept clean.


straight chimney installation




isolated chase chimney installation




minimum chimney height



For Masonry chimney must comply with CAN/ULC-S629 OR BE CODE COMPLIANT MASONRY CHIMNEY



pitched roof



flat roof

This appliance must be installed with a listed 6"/153 mm and 7"/178.5 mm chimney system approved under the following standards: CAN-ULC S629(IN CANADA) OR UL 103HT(IN U.S.).

MAINTAIN CLEARANCES TO COMBUSTIBLES AS SPECIFIED IN THE CHIMNEY MANUFACTURERS

INSTALLATION INSTRUCTIONS. YOU MUST FOLLOW THE CHIMNEY MANUFACTURER'S INSTALLATION INSTRUCTIONS FOR INSTALLATION OF ALL CHIMNEY COMPONENTS.

USE APPROPRIATE SUPPORTS, CAPS, FLASHING AND SHIELDS IN ACCORDANCE WITH THE CHIMNEY MANUFACTURERS INSTALLATION INSTRUCTIONS.

CAUTION: THE STRUCTURAL INTEGRITY OF THE FLOOR, WALL AND CEILING/ROOF MUST BE MAINTAINED.


NOTE:

Do not install the chimney directly at the outlet of the appliance. A chimney connector is required. This is supplied with the appliance.

4.4 CONVECTION

Circulation of convection air

The convection air enters into the wood stove via the inlet at the bottom of the wood stove. The hot air for convection comes out of the wood stove via the front outlet and the top outlet.



5. FINISHING

5.1 BRICKS AND BAFFLES
INSTALLATION

WARNING

OPERATION OF THE APPLIANCE WITHOUT THE BAFFLES CAN RESULT IN EXCESSIVE TEMPERATURES THAT COULD DAMAGE THE APPLIANCE, CHIMNEY AND THE SURROUNDING ENCLOSURE.

NOTE: DO NOT OPERATE IF BAFFLE AND MANIFOLD SHIELD ARE NOT IN POSITION.

article designation	assembly sequence	art. no.	quantity	price group
individual bricks				
base brick, front	1+2	1017402	2	C
side wall brick	7+8	1017459	2	B
base brick, rear	3+4	1017403	2	B
rear wall brick	5+6	1019883	2	B
baffle plate	9	1019710	1	D
complete set (without baffle plate)				
set bottom	-	1017638	4	price list
wall set	-	1047756	4	price list
Attention: Surcharge according to price list when ordering in eboris 1300 - black				

article designation	assembly sequence	art. no.	quantity	price group
individual bricks				
base brick, front	1+2	1017404	2	C
side wall brick	7+8	1017461	2	B
base brick, rear	3+4	1017405	2	C
rear wall brick	5+6	1017462	2	D
baffle plate	9	1019711	1	D
complete set (without baffle plate)				
set bottom	-	1017639	4	price list
wall set	-	1047758	4	price list
Attention: Surcharge according to price list when ordering in eboris 1300 - black				

5.2 DOOR REMOVAL / INSTALLATION



WARNING

BURNING YOUR APPLIANCE WITH THE DOORS OPEN OR AJAR CREATES A FIRE HAZARD THAT MAY RESULT IN A HOUSE AND/OR CHIMNEY FIRE.

DO NOT STRIKE OR SLAM DOOR.

NEVER REMOVE THE DOOR WHEN THE APPLIANCE IS HOT.

Please follow the following steps to dismantle / install the firebox door. Take care when carrying out these tasks as otherwise damage to the casing / door cannot be ruled out. We recommend protecting the casing / metal plates with an overlay.

Dismantling:

1. Use a screwdriver or a similar tool to remove the safety clasp on the stop-per side (hinge side) of the door.



2. Swing the door open. Then tighten the Allen screw on the lower hinge with a 3 mm Allen key.



3. Take hold of the door at the bottom. Raise the door a little with a light lifting movement so that the lower pin of the hinge is exposed.



4. In this position, pull the door a little forward at the bottom.



5. Now allow the door to drop down a little so that it comes away from the upper guidance pin and can be removed.

The door is now free and can be carefully placed to one side.



INSTALLATION: Installation is carried out in the reverse order:

1. Firstly guide the door in a slightly inclined position onto the fixture for the hinge side of the door. In the process, support the door from below so that the fireplace casing is not scratched.



2. Then swing the door inwards and set the lower pin into the lower fixture. To ensure the hexagonal socket can slide into the fixture, move the door a little (swivel the door).



3. Loosen the hexagonal socket on the lower hinge with a 3 mm Allen key.

4. Close the door and then push the safety clasp back onto the pin.

6. OPERATION



ALWAYS OPERATE THIS APPLIANCE WITH THE DOOR CLOSED AND LATCHED EXCEPT DURING START UP AND RE-FUELING. ALWAYS WEAR GLOVES TO PREVENT INJURY. DO NOT LEAVE THE FIRE UNATTENDED WHEN THE DOOR IS UNLATCHED AS UNSTABLE WOOD COULD FALL OUT OF THE FIRE CHAMBER CREATING A FIRE HAZARD TO YOUR HOME.

PLEASE USE THE GLOVE THAT IS SUPPLIED WHEN OPERATING THE MODULE.

NEVER EVER LEAVE CHILDREN UNATTENDED WHEN THERE IS A FIRE BURNING IN THE APPLIANCE. NEVER USE GASOLINE, GASOLINE-TYPE LANTERN FUEL, KEROSENE, CHARCOAL LIGHTER FLUID, OR SIMILAR LIQUIDS TO START OR 'FRESHEN UP' A FIRE IN THIS APPLIANCE. KEEP ALL SUCH LIQUIDS WELL AWAY FROM THE APPLIANCE WHILE IT IS IN USE.

OBJECTS PLACED IN FRONT OF THE APPLIANCE SHOULD BE KEPT A MINIMUM OF 48" FROM THE FRONT FACE.

ANY MODIFICATION OF THE APPLIANCE THAT HAS NOT BEEN APPROVED IN WRITING BY THE TESTING AUTHORITY IS CONSIDERED BREACHING CSA B365 (CANADA) AND ANSI NFPA 211 (USA).

Open air control if adjustable and damper if fitted before opening firing door.

HOT WHILE IN OPERATION. KEEP CHILDREN, CLOTHING AND FURNITURE AWAY. CONTACT MAY CAUSE SKIN BURNS. WEAR SUITABLE GLOVES TO OPERATE YOUR APPLIANCE.

DO NOT POKE OR STIR THE LOGS WHILE THEY ARE BURNING. USE ONLY FIRELOGS THAT HAVE BEEN EVALUATED FOR THE APPLICATION IN FIREPLACE AND REFER TO FIRELOG WARNINGS AND CAUTION MARKINGS ON PACKAGING PRIOR TO USE.



WARNING

AVOID BURN RISK. REMOVE OPERATIONAL TOOL AFTER USE!!!



WARNING

PLEASE USE THE GLOVE THAT IS SUPPLIED WHEN OPERATING THE MODULE!

Your Spartherm product is designed with the most advanced technology. The appliance is extremely airtight. It has an exclusive direct outside air supply (optional kit), a safety feature designed to prevent spillage, and to keep your house free of carbon monoxide, in case of a down drafting chimney or an internal negative pressure.

The first fire(s) in your appliance will be difficult to get going and keep going with little amount of heat being generated. This is a result of the moisture being driven out of the fire brick. Allow 30 hours of hot fires (temperatures in excess of 500°F / 260°C - 600°F / 316°C) before your appliance will perform normally. During the break-in period (the first 2 or 3 fires) create only small, hot fires using kindling; this will allow the firebrick to cure. Do not be alarmed if small hairline cracks develop in the firebrick. This is a normal occurrence and does not pose a safety hazard. The paint may also smell for the first few fires as it cures and it is recommended to open a door or window to alleviate the smell.

To start, a brisk fire is required. Place loosely crumpled paper on the floor of the appliance and cover with dry kindling. Light the paper and leave the door slightly ajar (one inch) until all kindling is burning. To maintain a brisk fire, a hot coal bed must be established and maintained.

Slowly add larger wood (2x4 size pieces). Lay the pieces lengthwise from side to side in the hot coal bed with a shallow trench between, so that the primary air can flow directly into this trench and ignite the fuel above. When the fire seems to be at its peak, medium sized logs may be added. Once these logs have caught fire, carefully close the door. (Closing the door too quickly after refueling will reduce the firebox temperature and result in an unsatisfactory burn.) Remember it is more efficient to

burn medium sized wood, briskly, and refuel frequently than to load the appliance with large logs that result in a smouldering, inefficient fire and dirty glass. As soon as the door is closed, you will observe a change in the flame pattern. The flames will get smaller and lazier because less oxygen is getting into the combustion chamber. The flames, however, are more efficient. The flames will remain lazy but become larger again as soon as the firebricks have been heated thoroughly and the chimney becomes heated and provides a good draft. At this point, the roaring fire that you see when the door is opened is wastefully drawing heated room air up the chimney -- certainly not desirable. Always operate with the door fully closed once the medium sized logs have caught fire. You can now add larger pieces of wood and operate the appliance normally. Once the appliance is entirely hot, it will burn very efficiently with little smoke from the chimney. There will be a bed of orange coals in the firebox and secondary flames flickering just below the top firebrick. You can safely fill the firebox with wood up to the air inlet on the backside of the firebox or, if not present, up to 50% of the fireboxes backside height and will get best burns if you keep the appliance pipe temperatures between 250°F (120°C) and 450°F (270°C). A surface thermometer placed on the front top will help regulate this.

Without an appliance thermometer, you are working blindly and have no idea of how the appliance is operating! An appliance thermometer offers a guide to performance.

Can't get the fire going?

Use more kindling and paper. Assuming the chimney and vent are sized correctly and there is sufficient combustion air, the lack of sufficiently dry quantities of small kindling is the problem. Thumb size is a good gauge for small kindling diameter.

Can't get heat out of the appliance?

One of two things may have happened. The appliance door may have been closed prematurely and the appliance itself has not reached optimum temperature. Reopen the door and/or draft control to re-establish a brisk fire. The other problem may have been wet wood. The typical symptom is sizzling wood and moisture being driven from the wood.

ADJUSTING THE COMBUSTION AIR.

LUXUS® FS24 V / FS 28 V are equipped with an air control system that is easy and effective to use. The air control system is designed to give you the ability to adjust the "COMBUSTION AIR" in such a way that you have a fire that burns clean and well. It is important to ensure that the combustion air used to create a clean burning fire... as per the following INFORMATION.

Air Wash system:

This combustion air is designed to keep the glass clean and to feed the fire with combustion air to burn. The further the lever is to the right the more air is made available for the fire. As an example this setting would be used when you first light the fire or when you reload the fire. Depending on the type of fire that you require you would adjust the air to either slow down the fire -- moving to the midway mark -- or to slow the fire even more as you move to the left past the midway mark. It is important not to "choke" the fire -- do not starve the fire of air as it can create smoke and a dirty burn. It can also result in dirty glass and an inefficient fire.

Secondary Air system:

This air is used to burn off the gases that are released when the fire burns. The secondary air is also linked to the lever and is adjusted as you adjust the fire.

Caution:

Never close the air lever of the air control completely or before the fire has started to burn efficiently as it will create smoke and the fire would be inefficient and the energy from the wood is wasted. The door should be closed during operation.
Please follow the instructions in the manual to get the best results from your module.

WARNING!!!


**HOT GLASS – WILL CAUSE BURNS.
DO NOT TOUCH GLASS UNTIL COOLED
NEVER!!! ALLOW CHILDREN TO TOUCH THE GLASS.**

PLEASE NOTE

The tool that has been provided is for the operation of the air control lever and for opening and closing the wood stove door.

WARNING!

If this tool is not used there is a risk of BURNS.



A - Air supply open:

(when lighting the fire or adding new wood). The control lever is pushed completely to the right. The firebox will now receive the maximum volume of combustion air and secondary air.

B - Controlled burning:

Control lever approx. 20 mm further than the closed air supply position. This ensures that the fire does not receive too much air and the wood does not burn too quickly. The secondary air flows over the panel ventilation system to the ceramic glass panel and prevents, as far as possible, any sooting of the glass panel.

C - Air supply closed:

Control lever in the limit position of the 20 mm wide spacer. The firebox receives no combustion air in this setting.



WARNING

The combustion-air damper should NOT be altered for increased firing for any reason!




WARNING

DO NO SHUT OFF THE COMBUSTION AIR OFF WHILE THE FIRE IS BRUNING OR WHILE THERE ARE STILL GLOWING COALS IN THE FIREBOX!

DOOR ASSEMBLY – SPARE PARTS.

ROBAX 4 MM CERAMIC GLASS.

USE ONLY AS PER MANUFACTURERS STANDARD AND SPARE PARTS.



Pos.	name	quantity	SAP
1	door profile	1	-
2	glass strip, top	1	-
3	glass strip, bottom	1	-
4	lock	1	-
5	handle	1	-
6	bush	2	-
7	glass	1	-
8	seal / gasket	2	-
9	seal / gasket	2	-
10	seal / gasket	1	-
11	spring, left	1	-
12	door support, bottom	1	-
13	cheese head screw M4x5	1	-
14	fillister head screw	8	-
15	countersunk bolt M5x10	1	-
16	set screw M5x8	1	-

6.1 FIRE EXTINGUISHERS / SMOKE DETECTORS

All homes with a solid fuel burning appliance should have at least one fire extinguisher in a central location, known to all, and at least one smoke detector in the room containing the appliance. If it sounds an alarm, correct the cause but do not de-activate or relocate the smoke detector.

6.2 FUEL



WARNING

OUR MODULAR FREESTANDING STOVES ARE DESIGNED TO BURN NATURAL WOOD ONLY. DO NOT BURN TREATED WOOD, COAL, CHARCOAL, COLOURED PAPER, CARDBOARD, SOLVENTS OR GARBAGE. THIS APPLIANCE HAS NOT BEEN TESTED WITH AN UNVENTED GAS LOG SET. TO REDUCE RISK OF FIRE OR INJURY, DO NOT INSTALL AN UNVENTED GAS LOG SET INTO THE APPLIANCE.

HIGHER EFFICIENCIES AND LOWER EMISSIONS GENERALLY RESULT WHEN BURNING AIR DRIED SEASONED HARDWOODS, AS COMPARED TO SOFTWOODS OR TOO GREEN OR FRESHLY CUT HARDWOODS. DO NOT BURN GREEN OR FRESHLY CUT WOOD.

BURNING WET UNSEASONED WOOD CAN CAUSE EXCESSIVE CREOSOTE ACCUMULATION. WHEN IGNITED IT CAN CAUSE A CHIMNEY FIRE THAT MAY RESULT IN A SERIOUS HOUSE FIRE.

DO NOT STORE FUEL WITHIN THE CLEARANCE TO COMBUSTIBLES, OR IN THE SPACE REQUIRED FOR RE-FUELING AND ASH REMOVAL.

When loading the appliance, ensure that the upper fibre baffles are not forced out of position. For maximum efficiency, when the appliance is thoroughly hot, load it fully to the line of air inlet nozzles at the backside of the firebox or, if not present, to 50% of the fireboxes backside

height and burn at a medium low setting. The whiteness of the bricks and the cleanliness of the glass are good indicators of your operating efficiency. Not enough heat is produced when only a few pieces of wood are burned or the wood may not burn completely. Fuel for the appliance must not be stored closer than the required clearances to combustibles (heat sensitive material).

NEVER STORE WOOD IN THE ASH PAN COMPARTMENT (IF APPLICABLE).

NOTE: WHEN LOADING THE APPLIANCE, ENSURE TO KEEP FUEL BACK FROM THE GLASS. IF COALS ARE TO ACCUMULATE ON THE FRONT LIP, THERE IS A CHANCE THEY WILL FALL OUT WHEN THE DOOR IS OPENED.


Burn only dry, clean unpainted wood that has been seasoned. It produces more heat and less soot or creosote. Freshly cut wood contains about 50% moisture while after proper seasoning only about 20% of the water remains. As wood is burned, this water boils off consuming energy that should be used in heating. The wetter the wood, the less heat is given off and the more creosote is produced. Dry firewood has cracks in the end of the grain. Both hardwood and softwood burn equally well in this appliance but hardwood is denser, will weigh more per cord and burn a little slower and longer.

Firewood should be split, stacked in a manner that air can get to all parts of it and covered in early spring to be ready for burning that fall. Dry firewood has cracks in the end grain.

Cut the wood so that it will fit horizontally, front to back, making for easier loading and less of a likelihood that the wood will roll onto the glass.

Manufactured firelogs made by compressing 100% natural wood fibre can be safely used as fuel. Do not use manufactured firelogs if they contain additives such as paraffin, wax, binders etc. Never burn more than two manufactured firelogs at a time.

Do's	Dont's
• Build a hot fire.	• Take ash out immediately. Let it accumulate to a depth of at least one inch. A good ash layer provides for a longer lasting and better burning fire.
• Use only dry wood.	• Burn wet wood
• Several pieces of medium sized wood are better than a few big pieces.	• Close the door too soon or damper down too quickly. Burn one large log rather than two or three smaller, more reasonably sized logs.
• Clean chimney regularly.	• Burn at continually "low setting", if glass door is constantly blackened. This means the Firebox temperature is too low and energy is wasted by incomplete combustion.
• Refuel frequently using medium sized wood.	



6.3 LIGHTING A FIRE

Lighting the fire in your wood stove is very easy if you follow the instructions given below:

1. A fire may only be started in the wood stove when the firebox lining has been correctly installed.
2. Turn off any air extraction ventilation (kitchen, bathroom, WC etc.). This will avoid low pressure building up in the installation room that can affect the extraction of flue gases from the wood stove. Check the combustion air supply (if required, open the cover flap!)
3. Adjust the combustion air regulator to the far right, and open the firebox door (swing open).
4. Place chopped wood into the middle of the firebox using the funeral pyre method (use softwood).
Caution: The height of the wood pile must not exceed the lower marking on the deflector plate!
5. Place standard firelighter cubes under the wood pyre to help start the fire. (paper is not recommended because it burns too quickly and causes ash to circulate).
6. Never use methylated spirits, petrol, oil or other easily combustible liquids.
7. Light the fire using the firelighter cubes and, if required, leave the firebox door open by approx. 3-5 cm. The fire should now light, burning brightly and intensively.
8. When the kindling wood is burning well, add smaller hardwood logs or larger softwood logs using the funeral pyre method and close the door.
9. When the wooden logs are burning well, the air control lever can be set to a position in the middle.
10. You can find out more about the correct volume of wood to add to the fire in the section "Volume of wood to add per hour".
11. When the wood has been completely burnt and only embers are remaining from the initial wood added to the fire, new wood can now be added as required (hardwood is ideal).
12. Depending on the weather conditions, adjust the control lever towards the middle setting or a little over. The correct setting is always based on experience and the current local conditions.
13. Always open the firebox door slowly. This will ensure

that you avoid sudden low pressure in the firebox and prevent exhaust gases leaking into the living room.

14. This will prevent any possible smoke leakage through the opened door when adding new wood during the ember phase.

15. Never consistently add more wood than the recommended amount.


Caution: The height of the wood pile must not exceed the lower marking on the deflector plate!

6.3.1 FLASH FIRE

A flash fire is a small fire burned quickly when you don't need much heat. After your kindling has "caught", load at least 3 pieces of wood, stacked loosely. Burn with the draft control fully open if adjustable or open the door upward with 1.5 inches for 3 minutes if required.

6.3.2 EXTENDED FIRE

Load your larger pieces of wood compactly, packed close enough to prevent the flames from penetrating it completely.



DO NOT OVERFIRE THE APPLIANCE!
OVERFIRING CAN OCCUR BY:

- A. Burning large amounts of smaller wood pieces such as furniture scraps, skids or treated wood.
- B. Operating the appliance with a poor gasket seal on the main door.
- C. Overfilling your appliance. Go by the following specifications:

Appliance	Wood consumed per hour
LUXUS® FS24 V	1.8 kg/hr
LUXUS® FS28 V	2.1 kg/hr

7. MAINTENANCE

! WARNING

APPLIANCE MAY BE HOT, DO NOT SERVICE UNTIL APPLIANCE HAS COOLED. DO NOT USE ABRASIVE CLEANERS.

Check your chimney and chimney connector for creosote and soot buildup weekly until a safe frequency for cleaning is established.

If accumulation is excessive, disconnect the appliance and clean both the chimney and the appliance. You may want to call a professional chimney sweep to clean them. Both have to be cleaned at least once a year or as often as necessary.

Remove baffle plates and clean above them once a year. Replace any broken bricks.

7.1 ASH REMOVAL PROCEDURES

! WARNING

IMPROPER DISPOSAL OF ASHES RESULTS IN FIRES. DO NOT DISCARD ASHES IN CARDBOARD BOXES. DUMP IN BACK YARDS, OR STORE IN GARAGES.

IF USING A VACUUM TO CLEAN UP ASHES, BE SURE THE ASHES ARE ENTIRELY COOLED. USING A VACUUM TO CLEAN UP WARM ASHES COULD CAUSE A FIRE INSIDE THE VACUUM.

Allow the ashes in your firebox to accumulate to a depth of two or three inches; they tend to burn themselves up. When the fire has burned down and cooled, remove any excess ashes but leave an ash bed approximately 1" (25 mm) deep on the firebox bottom to help maintain a hot charcoal bed.

Shovel some ashes out through the door into a metal container with a tight fitting lid. Leave an ash bed approximately 1" (25 mm) deep on the firebox bottom to help maintain a hot charcoal bed. Keep the closed container on a noncombustible floor or ground, well

away from all combustible materials. The ashes should be retained in the closed container until all cinders have thoroughly cooled. The container that is used to remove the hot coals/ashes will be moved outdoors immediately and NO other waste shall no placed in this container.

7.2 CREOSOTE FORMATION AND REMOVAL

When wood is burned too slow, it produces tar and other organic vapors, which combine with expelled moisture to form creosote. The creosote vapors condense in the relatively cooler chimney flue of a slow-burning fire. As a result, creosote residue accumulates on the flue lining. When ignited this creosote makes an extremely hot fire. The chimney connector and chimney should be inspected at least once every two months during the heating season to determine if a creosote buildup has occurred. If creosote has accumulated it should be removed to reduce the risk of a chimney fire.

7.3 RUNAWAY OR CHIMNEY FIRE

! WARNING

A CHIMNEY FIRE CAN PERMANENTLY DAMAGE YOUR CHIMNEY SYSTEM. THIS DAMAGE CAN ONLY BE REPAIRED BY REPLACING THE DAMAGED COMPONENT PARTS. CHIMNEY FIRES ARE NOT COVERED BY THE WARRANTY.

CAUSES:

- Using incorrect fuel, or small fuel pieces which would normally be used as kindling.
- Leaving the door ajar too long and creating extreme temperatures as the air rushes in the open door.
- Improperly installed or worn gaskets.
- Creosote build up in chimney.

SOLUTIONS:

- Do not burn treated or processed wood, coal, charcoal, coloured paper or cardboard.
- Do not burn green or freshly cut wood.
- Be careful not to overfire the appliance by leaving the door open too long after the initial start-up. A

7.5 GLASS REPLACEMENT



DO NOT USE SUBSTITUTE MATERIALS

GLASS MAY BE HOT, DO NOT TOUCH GLASS UNTIL COOLED.

CARE MUST BE TAKEN WHEN REMOVING AND DISPOSING OF ANY BROKEN DOOR GLASS OR DAMAGED COMPONENTS. BE SURE TO VACUUM UP ANY BROKEN GLASS FROM INSIDE THE APPLIANCE BEFORE OPERATION.

DO NOT STRIKE, SLAM OR SCRATCH GLASS. DO NOT OPERATE APPLIANCE WITH GLASS REMOVED, CRACKED, BROKEN OR SCRATCHED.

Installation:

Remove the door from the stove and remove the glass retainer. Position the 4 mm ceramic Schott Robax glass in the door, make sure that the glass gasket will properly seal your unit, and replace the retainer, it should rest on the gasket not the glass. Tighten securely, but do not wrench down on the glass as this may cause the glass to break. Replacement Glass Part as for unit.

7.6 CARE OF GLASS

If the glass is not kept clean permanent discolouration and / or blemishes may result. Normally a hot fire will clean the glass. The most common reasons for dirty glass include: not using sufficient fuel to get the appliance thoroughly hot, using green or wet wood, closing the draft so far that there is insufficient air for complete combustion.

7.7 CLEANING THE GLASS CERAMIC SHEET



THE GLASS CERAMIC SHEET MAY ONLY BE CLEANED WHEN COLD (FIREPLACE Module NOT BURNING AND COOLED DOWN; NO HOT ASH IN THE FIRE CHAMBER).



All Spartherm modules are supplied with Robax glass in the door.



**HOT GLASS WILL CAUSE BURNS.
DO NOT TOUCH GLASS UNTIL COOLED. NEVER
ALLOW CHILDREN TO TOUCH GLASS.**

Robax is a ceramic glass.

Do not use substitute glass and order replacement glass from Spartherm through your dealer.

7.8 CARE OF PLATED PARTS

If the appliance is equipped with plated parts, you must clean fingerprints or other marks from the plated surfaces before operating the appliance for the first time. Use a glass cleaner or vinegar and towel to clean. If not cleaned properly before operating for the first time, the marks can cause permanent blemishes on the plating. After the plating is cured, the fingerprints and oils will not affect the finish and little maintenance is required, just wipe clean as needed. Prolonged high temperature burning with the door ajar may cause discolouration on plated parts.

NOTE: The protective wrap on plated parts is best removed when the assembly is at room temperature but this can be improved if the assembly is warmed, using a hair dryer or similar heat source.

8. REPLACEMENTS

Contact your dealer or the factory for questions concerning prices and policies on replacement parts. Normally all parts can be ordered through your Authorized dealer / distributor. FOR WARRANTY REPLACEMENT PARTS, A PHOTOCOPY OF THE ORIGINAL INVOICE WILL BE REQUIRED TO HONOUR THE CLAIM. When ordering replacement parts always give the following information:

- Model & Serial Number of appliance
- Installation date of appliance
- Part number
- Description of part
- Finish

IDENTIFIES ITEMS WHICH ARE NOT ILLUSTRATED. FOR FURTHER INFORMATION, CONTACT YOUR AUTHORIZED DEALER.



FAILURE TO POSITION THE PARTS IN ACCORDANCE WITH THIS MANUAL OR FAILURE TO USE ONLY PARTS SPECIFICALLY APPROVED WITH THIS APPLIANCE MAY RESULT IN PROPERTY DAMAGE OR PERSONAL INJURY.

thermometer on the chimney connector and/or appliance top helps.

- Replace worn, dried out (inflexible) gaskets.
- Have chimney regularly cleaned.

IN CASE OF A CHIMNEY FIRE:

Have a well understood plan for evacuation and a place outside for everyone to meet. Prepare to evacuate to ensure everyone's safety.

Close air control on appliance.

Call local fire department. Have a fire extinguisher handy.

Contact local authorities for further information on how to handle a chimney fire.

After the chimney fire is out, clean and inspect the chimney or chimney liner for stress and cracks prior to lighting another fire. Also check combustibles around the chimney and the roof.

7.4 CHIMNEY CLEANING

Both the chimney and the appliance must be inspected and cleaned at least once a year.

For serious wood burners, chimney cleaning must be done as needed to avoid chimney fires; the venting systems for controlled combustion appliances may need cleaning as often as once a month. These rates, however, depend on the burning habits of the individual operating the appliance. For example, it is possible to clog a solid fuel appliance chimney in a few days if slow, smoldering fires are burned and the chimney is cold. NOTE: Appliances burned consistently without hot fires may result in significant creosote accumulations in the chimney.


Certain items and considerations are important in chimney cleaning:

- Proper tools should be used, including a brush specifically designed for chimney cleaning.
- The chimney connector and dampers as well as the chimney should be cleaned.
- The appliance's firebox and baffle system should be cleaned if needed.
- The chimney should be inspected and repairs made if needed, preferably by a qualified chimney sweep or mason.

8.1 EXPLODED VIEW

NOTICE:

Please refer to the following drawing and specify the spare part number and WHICH UNIT SIZE YOU HAVE FOR REPLACEMENTS



ACCESSORIES

1	Frame
2	Firebox door with ceramic glass
3	Firebox lining
4	Firebox
5	Exhaust gas sockets, rotatable (vertically or horizontally)
6	Convection air jacket
7	Combustion air sockets, outlet to rear

Modular Freestanding Stoves Description Part			
Stove LUXUS FS® 24 V	Stove LUXUS FS® 28 V		Optional Com-bustion Air Appliance Connector
	Required Accessories Base A 1065248		Required Accessories Base A 1047525
	Base B 1065249		Base B 1047526
Base C 1065250		Base C 1047527	
		5" Butterfly Valve	

9. TROUBLESHOOTING



APPLIANCE MAY BE HOT, DO NOT SERVICE UNTIL APPLIANCE HAS COOLED.

DO NOT USE ABRASIVE CLEANERS.

Problem	Solution
Can't get the fire started.	• Not enough kindling / paper? Add more. • Not enough air? Ensure air control is fully open. Also ensure that the air opening is not obstructed. • Cold air blockage? Burn a piece of paper to establish a draft. • Use dry seasoned wood. • Flue blockage? Inspect chimney.
Smokes when door is open.	• Cold air blockage? Burn a piece of paper to establish a draft. • Insufficient draft? Add more pipe. • Let air stabilize before opening door. • Ensure baffles are positioned correctly. • Negative pressure? Open a window near the appliance.
Appliance emits odour.	• Paint curing. See "GENERAL INSTRUCTIONS" section.
Stove doesn't burn hot enough.	• Wood is too wet. • Insufficient draft? Add more pipe. • Not enough air? Ensure air control is fully open. Also ensure that the air opening is not obstructed.
Wood burns too fast.	• Air control may need to be adjusted down. • Check door gasket for adequate seal. • Wood may be extremely dry.
Dirty glass.	• Air control may be closed too far. Open air control more. • Burn hotter, smaller fires. Use well seasoned wood.

10. GENERAL WARRANTY TERMS AND CONDITIONS

10.1 GENERAL INFORMATION

This quality manufactured product is state of the art. The materials used were meticulously selected and are constantly checked, as is our entire production process.

Setting up or installing this product requires specialized knowledge. Our products may therefore only be installed and commissioned by specialized firms and in compliance with statutory regulations as amended.

10.2 WARRANTY PERIOD

The General Warranty Terms and Conditions apply only within the USA and Canada. The warranty period and scope of the warranty in accordance with these terms and conditions shall apply apart from the statutory guarantee, which remains unaffected.

Spartherm Feuerungstechnik GmbH gives a 5-year warranty on: Basic body modular freestanding stove

Spartherm Feuerungstechnik GmbH gives a 24-month warranty on elevating mechanisms, operating devices such as handles, adjustment levers, shock absorbers, electronic and electrical components such as exhausters, governors, original spare parts, all purchased parts and safety devices.

Spartherm Feuerungstechnik GmbH gives a 6-month warranty on wearing parts around the fire, such as refractory bricks, vermiculite, fire grates, seals and glass ceramics.

10.3 REQUIREMENT OF EFFECTIVENESS FOR THE WARRANTY

The warranty period starts on the date of delivery to the dealer / intermediary. This must be verified from a document such as an invoice with the dealer / intermediary's confirmation of delivery. The warranty certificate relating to the product must be produced by the claimant when making a warranty claim.

If such proof is not produced Spartherm Feuerungstechnik GmbH shall not be obliged to honour the warranty.

10.4 WARRANTY EXCLUSIONS

The warranty does not cover:

- wear and tear to the product
- Refractory bricks/ vermiculite:

These are natural products subjected to expansion and contraction during the heating process. This may create cracks. For as long as the linings remain in position in the fire chamber and do not break up, they remain fully functional.

- the Surfaces:

Discoloration of the enamel or galvanized surfaces caused by thermal stress or overload.

- the elevating mechanism:

If the installation instructions are not correctly followed, resulting in overheating of the pulleys and bearings.

- the seals:

Reduced sealing due to thermal stress and hardening.

- the ceramic glass

Soiling caused by soot or burnt-in residues of burnt materials as well as visibly changed colour or other aspects due to thermal stress.

- improper transport and/or incorrect storage
- improper handling of fragile components such as glass and ceramics
- improper handling and/or use
- lack of maintenance
- incorrect installation or connection of the unit
- Non-observance of the installation and operating instructions
- technical modifications to alter the unit by third parties
- installation that does not comply with industry practice on installation instructions

10.5 NOTE

Your specialist dealer/contractor will gladly advise and assist you in matters not covered by our warranty terms and conditions and undertakings. We particularly advise you to have your wood stove module/stove serviced regularly by a stove fitter.

Technical data subject to change errors and omissions excepted.



EN Your specialist dealer | FR Votre revendeur spécialisé



Spartherm Feuerungstechnik GmbH | Maschweg 38 | GER - 49324 Melle